

DO LESS.

Centargo minimizes your injector touch time by automating manual processes.

CARE MORE.

Centargo helps you focus on what matters most in every CT scan – the patient.



With Efficiency.

Centargo is designed for a simple, reliable and automated workflow, easy daily set-up and quick change time between scans.

Centargo's

daily set-up process can be completed in under 2 minutes.



24-hour use

The simple snap-in patient line auto-primes upon insertion and is ready for the next patient in less than 20 seconds.



One click

With Confidence.

Less manual data entry and the intuitive user interface help you confidently complete your daily tasks.



medrado Centargo

Touch screen
within the
scan room
so that you
can be close
to your patient.



The bar code reader reduces manual data entry and provides easy traceability and access to contrast and injection details.*

With Centargo.

For easy set-up and patient-to-patient change over:

- Pre-assembled 24-hour Day Set with optional replaceable spikes
- > Fast changeover using snap-in Patient Line

Designed with safety in mind:

- ➤ Inlet and outlet air detection in addition to automatic air removal within reservoirs
- > Recessed connection on the Day Set
- > Two check valves in the Patient Line

Together with excellent performance:

- > Piston-based fluid delivery
- > Heat maintainers for contrast reservoirs

And modern convenience:

- > Integrated prime container
- > Dual screen configuration within scan and control room
- > Training videos on Control Room Unit
- > VirtualCare™ for remote monitoring, updates, and diagnostics

With Workflow Solutions.

- > Integrated barcode reader for contrast data capture
- Automated Documentation for access to contrast and injection information in PACS
- Smart Protocols to calculate individualized injection protocols
- Advanced Scanner Connectivity for protocol exchange and device synchronization



With Quality.

Centargo offers the Bayer MEDRAD® quality that you have come to trust.

- Piston-based fluid delivery and personalized contrast media protocol software.*
- >Three inlet air sensors and one outlet air sensor as well as reservoir air detection and automatic air removal.
- Cordless mobility through a battery powered, Wi-Fi enabled configuration.

Think ahead. Plan ahead. Stay ahead. Bayer is your partner for peace of mind and patient care.

With Bayer.

Bayer relies on our decades of experience, comprehensive service networks, expert clinical support and dedicated sales teams to make sure that you receive the solutions you need to improve your efficiency, confidence and quality.



^{*}P3T® and Protocol Assistant Software

System Specifications

Description	Specification
Volume Range	1 mL to 200 mL for contrast and flush phases; 1 mL to 400 mL for DualFlow phases (in 1 mL increments)
Flow Rate Range	0.1 to 10 mL/sec in 0.1 mL/sec increments
DualFlow	Simultaneous injection of contrast and saline in increments of 5%
Patency Check / Test Inject	Real time flow rate adjustment and multi-phase test injections
Programmable Pressure Limit	From 50 psi to 300 psi in 1 psi increments (also displayable in kPa and kg/cm²)
Programmable Delay	1 second to 900 seconds in 1 second increments
Pause	Maximum pause time of 20 minutes
Fluid Loading	Contrast: 50 mL – 500 mL Saline: 50 mL to 1000 mL
Fluid Reservoirs (volume)	Three 200 mL reservoirs (two contrast and one saline)
Injection Capabilities	Maximum of 6 phases per injection. Maximum of 10 injections per exam
Fluid Delivery Method	Piston-based
Day Set	Pre-assembled, labeled for 24-hour use, designed for set-up in less than 2 minutes
Patient Line	250 cm, single hand design, two check valves, auto-primes upon insertion
Displays	Two independent, Wi-Fi enabled, full color, touch screen units with modern graphical user interfaces located in the scan room and control room
Air Detection	Three inlet air sensors and one outlet air sensor Includes reservoir air detection and automatic air removal
Battery Performance	Up to 16 hours or up to 60 injections
Integrated Prime Container (vol)	680 mL
Injector Dimensions (WxDxH)	76.2 x 68.6 x 167.6 cm
Injector Weight (approx.)	76 kg (Pedestal configuration)
Available Scanner Interface	ISI 700, ISI 900 and Connect.CT
Smart Protocols	P3T® algorithms calculate individualized injection protocols for cardiac CT, CT pulmonary angiography and CT imaging of abdominal organs Protocol Assistant provides basic protocol calculations for a range of procedure types
eGFR Calculator	Available on Control Room and Scan Room Units

Ordering Information

Injector Configurations

> Centargo Pedestal System with Batteries CENT-SYS-BAT > Centargo OCS System CENT-SYS-OCS

Disposables

> Centargo Day Set (24-hour use) CENT-DS > Centargo Patient Line CENT-PL > Centargo Replacement Spikes (optional) CENT-RS

Smart Protocols

> P3T Personalized Protocols CENT-P3T > PAT Protocol Assistant CENT-PAT

CENT-P3T-PAT

CENT-AUTO-DOC

Automated Documentation

> Modality Worklist **CENT-MWL** > PACS Interface **CENT-PACS**

Processing Productivity

> RIS Interface **CENT-RIS** > Dictation Interface CENT-SR > Radimetrics Interface CENT-REP

Scanner Connectivity

> ISI 900 **>** ISI 700 ISI2

> Connect.CT **CENT-ISI-CCT**



More information on radiology.bayer.com



Imaxeon Pty Ltd Unit 1, 38 - 46 South Street Rydalmere, NSW 2116 Phone: +1-61-2-8845-4999

Fax: +1-61-2-8845-4998 Imaxeon is a Bayer subsidiary



Authorized European Representative

Bayer Medical Care B.V. Avenue Céramique 27 6221 KV Maastricht The Netherlands Phone: +31 (0) 43-3585601 Fax: +31 (0) 43-3656598



Bayer reserves the right to modify the specifications and features described herein or to discontinue any product or notice or obligation. Please contact your authorized Bayer

displayed, modified or distributed without the express prior